



Product data sheet BodurCube / BCE and BCB / 3 mm housing*

BodurCube provides you with a bill deposit system that accepts the daily takings in the branch, stores them securely and issues a receipt for each deposit and cash box replacement. Laborious cash balancing with two-person control is consigned to the past. Besides streamlining processes, this substantially boosts staff safety and protects against robbery. Integration within continuous cash management processes, even control of the security transport companies or credit notes for your deposits, are also possible. The cash deposit system is easy to operate and extremely user-friendly.

Product Description – Standard

- ★ Available as bill and bundled bill system with one or two bill deposit boxes
- ★ Touchscreen menu navigation
- ★ Filling level monitor as a standard feature
- ★ Cash box replace monitor as a standard feature
- ★ Electronic lock as a standard feature
- ★ Cash box removal by two-person control as a standard feature
- ★ User hierarchy Administrator/User/CIT/Service
- ★ WEB interface to manage the system parameters as a standard feature
- ★ Storage of all transactions, incl. data (approx. 1 year)
- ★ Simultaneous handling of up to 6 currencies
- ★ Internet-ready
- ★ Operating system MICROSOFT WINDOWS POSREADY 7
- ★ Clear assignment of bills (amount) to cash box
- ★ Pre-set menu language (standard: D/E/I/F/P/RU/N)
- ★ Operating unit separate from the bill validator (under table assembly)
- ★ Prepared for floor and back wall anchoring

Product Description – Optional

- ★ Side system to accept and manage illegible bills and coins (in safe bags)
- ★ Adjustable numerical code lock
- ★ Security transport company lock – (one-time code)
- ★ Bill deposit box with a capacity of 2200 bills
- ★ Cash boxes with dye system
- ★ Integration in customer software ALVARA, Prosegur and SoftOne
- ★ Safe-in-safe installation
- ★ In-house assembly, training and installation
- ★ Service level agreement

* Please consult with your insurance provider in respect to an adequate insurance coverage.



Fig.: Bodur Cube / BCE — individual bill deposit system



Fig.: BodurCube / BCB — bundled bill deposit system



Fig.: BodurCube / BCB — bundled bill deposit system with 2 cash boxes



Fig.: BodurCube / BCB — bundled bill deposit system 2 cash boxes and side system



Product data sheet BodurCube / BCE and BCB / 3 mm housing*

Technical Data

Scope of delivery: 3mm housing – DIN right/operating unit/printer/bill deposit module with cash box/software incl. WEB interface/anchorage material

BCE – individual bill deposit system/1 cash box/3 mm

Dimensions when closed: 485 x 255 x 500 (H x W x L in mm)/keypad 30 mm protruding/deposit module 30 mm protruding/weight approx. 40 kg
Dimensions when open: 485 x 315 x 690 (H x W x L in mm)
Deposit speed: approx. 10 – 20 bills/min
Cash box information: 1 cash box/cash box capacity for approx. 1200 bills/cash box

BCE – individual bill deposit system/2 cash boxes/3 mm

Dimensions when closed: 485 x 380 x 500 (H x W x L in mm)/keypad 30 mm protruding/deposit module 30 mm protruding/weight approx. 65 kg
Dimensions when open: 485 x 475 x 805 (H x W x L in mm)
Deposit speed: approx. 10 – 20 bills/min
Cash box information: 2 cash boxes/cash box capacity for approx. 1200 bills/cash box

BCE – bundled bill deposit system/1 cash box/3 mm

Dimensions when closed: 485 x 255 x 500 (H x W x L in mm)/keypad 30 mm protruding/deposit module 100 mm protruding/weight approx. 40 kg
Dimensions when open: 485 x 315 x 690 (H x W x L in mm)
Deposit speed: approx. 50 – 60 bills/min
Cash box information: 1 cash box/cash box capacity for approx. 1200 bills/cash box

BCE – bundled bill deposit system/2 cash boxes/3 mm

Dimensions when closed: 485 x 380 x 500 (H x W x L in mm)/keypad 30 mm protruding/deposit module 100 mm protruding/weight approx. 65 kg
Dimensions when open: 485 x 475 x 805 (H x W x L in mm)
Deposit speed: approx. 80 – 100 bills/min
Cash box information: 2 cash boxes/cash box capacity for approx. 1200 bills/cash box

Side system for the BCE and BCB/3 mm

Dimensions when closed: 485 x 360 x 500 (H x W x L in mm)/mount 20 mm protruding/weight approx. 40 kg
Dimensions when open: 485 x 435 x 800 (H x W x L in mm)
Max. safe bag size: Safe bag 200 x 260 x 70 (H x W x L in mm)

* Please consult with your insurance provider in respect to an adequate insurance coverage.